



## SECTION VI

### **Health Hazard Data**

Primary Route of Entry: Skin or eye contact, inhalation.

Eye Contact: Direct contact with material can cause the following - substantial irritation - temporary corneal injury.

Skin Contact: The solvents in this material can cause moderate skin irritation.

Inhalation: Low acute toxicity expected on inhalation.

Ingestion: Tests on similar materials indicate a low order of acute oral toxicity.

Acute Overexposure: Tests on similar materials show a low order of acute oral and dermal toxicity. As a precaution, exposure to liquids, vapor, mists, or fumes should be minimized.

## SECTION VII

### **First Aid**

Eyes: Immediately flush eyes with a large amount of water for at least 15 minutes.

Skin: Wash affected skin areas thoroughly with soap and water. Remove and wash contaminated clothing thoroughly.

Ingestion: If ingested, do not induce vomiting and do not give liquids. Immediately obtain medical attention. Should a small amount accidentally enter mouth, rinse with water until taste is gone.

Inhalation: Move subject to fresh air. Give artificial respiration if breathing has stopped. Obtain medical attention if breathing problems persist.

## SECTION VIII

### **Special Protection Information**

Respiratory Protection: OSHA/NIOSH approved cartridge-type respirator.

Ventilation: Use local exhaust ventilation to capture vapor evolution. Provide ventilation sufficient to prevent exceeding OSHA PELs.

Eye Protection: Use safety glasses or face shield when eye contact may occur.

Skin Protection: Use chemical resistant gloves, boots, apron, and other impervious clothing to prevent skin contact.

Personal Hygiene: Do not eat, drink, or smoke in work areas. Remove contaminated clothing and launder or dry clean before reuse. Discard contaminated leather articles such as shoes and belt.

## SECTION IX

### **Spill or Leak Procedures**

Steps to be taken if material is released or spilled: Eliminate all ignition sources. Contain spill with inert materials. Keep spills and cleaning run-off out of sewers and open bodies of water. Take up with absorbent materials such as sand or sawdust and place in non-leaking containers. Large spills remove with a grounded pump to a salvage container.

Waste Disposal Method: Dispose of in accordance with all local, state and federal government regulations.

## SECTION X

### **Shipping Data:**

D.O.T. Shipping Name: Flammable, Liquid, N.O.S. (contains xylene)

Technical Shipping Name: Xylene

D.O.T. Hazard Class: 3 Flammable Liquid Packing Group: III

UN/NA Number: UN1993

D.O.T. Labels Required: 3 Flammable

Freight Class: 55