

LEGACY  
**Material Safety Data Sheet**

Date prepared: 4/26/10

Floor Wax™

**SECTION I - IDENTIFICATION**

**PRODUCT NAME:** Floor Wax™

**CHEMICAL FAMILY:** Floor Finish

**Manufacturer/Supplier:**

LEGACY A Division of Solomon Colors INC  
4050 Color Plant Rd  
Springfield Il 62704

**Emergency telephone no. (24h):** 800-624-0261

**DOT HAZARD CLASSIFICATION:** None

**HMIS RATING:** H = 1 - F=0 - R=0

The HMIS (Hazardous Materials Identification System) is a subjective rating system developed by the National Paint and Coating Association. Numerical ratings for health (H), flammability (F), and reactivity (R) are made using a scale of 0-4 where 0= no hazard, 1 = slight hazard, 2 = moderate hazard, 3 = high hazard and 4 = extreme hazard.

**SECTION II - INGREDIENTS AND IDENTITY INFORMATION**

% By WGT	MATERIAL	PEL	T.L.V.	CAS. NO.
<10%	Diethylene Glycol Ethyl Ether**	NE	NE	111 -90-0
<2%	Tributoxyethyl Phosphate	NE	NE	78-51-3
<50.0%	Acrylic Polymer	NE	NE	Not Hazardous
<8.0 %	Latex Emulsion	NE	NE	Not Hazardous
<8.0 %	Polyacrylic Dispersion	NE	NE	Blend

ONLY ITEMS MARKED \*\*ARE SARA TITLE III SEC 313 REPORTABLES. ALL INGREDIENTS ARE ON TSCA INVENTORY.

**SECTION III - PHYSICAL DATA**

BOILING POINT;	F 212
pH	8.0 to 9.0
SOLUBILITY IN WATER:	Miscible
EVAPORATION RATE (WATER = 1):	1
SPECIFIC GRAVITY:	1.03
PRODUCT FORM:	Liquid
APPEARANCE AND ODOR:	White Opaque Solution; Soft Scent

**SECTION IV - FIRE AND EXPLOSION DATA**

FLASH POINT:	>200 F
FLAMMABLE LIMITS	N/A
EXTINGUISHING MEDIA:	Foam, CO2, Dry Chemical, Water fog
SPECIAL FIREFIGHTING PROCEDURES:	Normal firefighting procedures
UNUSUAL FIRE OR EXPLOSION HAZARDS:	None known.

**SECTION V - REACTIVITY DATA**

STABILITY:	Stable
CONDITIONS TO AVOID:	None known.
INCOMPATIBILITIES:	Strong Acids, Alkalis and heavy metal salts.
HAZARDOUS DECOMPOSITION PRODUCTS	Normal products of combustion.
HAZARDOUS POLYMERIZATION:	Will not occur.

**SECTION VI - HEALTH HAZARD DATA**

ROUTE(S) OF ENTRY:	
EYES:	May cause mild irritation.

**Material Safety Data Sheet****Floor Wax™**

INITIATION? None Known  
SKIN: May cause mild irritation  
INGESTION: Non Known  
CARCINOGENICITY: NTP: NO IARC MONOGRAPHS: NO OSHA REGULATED: NO

**SIGNS AND SYMPTOMS OF OVEREXPOSURE:**

For Eyes: Redness or burning sensation. For Skin: Redness of skin or a warming sensation.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: None Known.

**FIRST AID PROCEDURES:**

For Eyes: Rinse immediately with plenty of water for 15 minutes, if condition persists see a physician.

For Skin: Wash contaminated area with soap and water.

For Ingestion: Give two large glasses of water. DO NOT induce vomiting and seek immediate medical attention.

**SECTION VII - SPILL OR LEAK PROCEDURES**

Personal Protection: Prevent contact with skin or eyes by wearing rubber gloves and approved safety glasses with side shields if splashing is likely to occur. Spilled material may be slippery under foot. Wear rubber boots with an anti-slip contact surface. Wear protective work clothing. Launder any contaminated clothing before reuse.

Environmental Protection Precautions: Do not release to the environment or water source.

Steps to be taken in case material is released or spilled: Halt spill at source and contain or dike spill with sand or inert absorbent material. Transfer any liquid to containers for recovery or disposal. Shovel used absorbent into drums for disposal in accordance with all applicable local and national regulations.

**SECTION VIII - EXPOSURE CONTROLS, PERSONAL PROTECTION**

Respiratory Protection: None required in well ventilated area.

Ventilation: Local exhaust: None required

Mechanical: (General): Provide adequate ventilation.

Protective gloves: Not normally necessary but should wear rubber gloves if contact with product is probable.

Eye protection: Not normally necessary but should wear approved safety glasses with side shields if any contact with eyes is possible.

Other Protective Equipment: Not normally needed. Launder contaminated clothing before reuse.

**SECTION X: STABILITY AND REACTIVITY**

Stability: Stable

Conditions to avoid: Temperatures of 212° F or over will boil water away.

Do not mix with acids or cationic materials.

Incompatibility: Treat as water.

Hazardous polymerization: Will not occur.

Hazardous Decomposition Products: Thermal decomposition on burning may produce toxic gases.

This product is not regulated under CERCLA or RCRA., Not reportable under SARA title III, section 311/312

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind expressed or implied.