

**Legacy Primer**<sup>™</sup>  
Characteristics and Applications

**Description**

Legacy Primer<sup>™</sup> is an entirely new concept in primers for cementitious materials. It prevents the concrete from absorbing water from the overlay material making it easier to spread and achieve a smooth surface. Also, Legacy Primer<sup>™</sup> is a reactive primer, remaining active for at least two hours after it is applied. It reacts and forms a chemical link between the overlay and the substrate. Legacy Primer<sup>™</sup> increases the bond strength by creating a more efficient chemical link between the concrete and the overlay.

**Features**

- “Reactive Primer”
- Easy application
- Greatly enhances bonding to concrete
- Prevents the sub floor from absorbing moisture from overlay
- Interior or exterior use
- Great for priming all masonry surfaces: concrete, tile, terrazzo, brick, and overlays.
- Overlay may be applied on Legacy Primer<sup>™</sup> whether it’s wet or dry for up to two hours.

**Surface Preparation**

Surface must be clean and free of contaminants, old polishes must be removed, and the floor must be completely dry before application. New concrete should be cured for at least 14 days. The floor should be adequately profiled via mechanical or chemical means to ensure proper bonding.

**Packaging**

40 lbs (18.9 L) 5 gallon

**Coverage**

Five gallons of Legacy Primer<sup>™</sup> should cover between 800 to 1200 square feet. Coverage will vary according to the porosity and composition of the floor material. Legacy Primer<sup>™</sup> is a ready to use product. It should not be diluted.

**Application**

Always test small area for compatibility and satisfactory bonding. Do not apply if ambient temperature is below 50 degrees. Legacy Primer<sup>™</sup> is compatible with all Legacy<sup>™</sup> overlay products and most other overlays. Once surface is properly prepared and dry, apply Legacy Primer<sup>™</sup> with a roller or sprayer. Apply evenly over entire surface. Apply a thin coat; if surface is very porous, a second coat may be necessary. Overlay can be applied immediately after primer placement, no lengthy drying time needed. The primer remains reactive for two hours, if two or more hours elapse, re-spray primer over affected area and then place overlay.

**Properties**

Coverage .....160-200 sq.ft./gal.  
Drying time.....30 - 60 minutes  
Leveling ..... Excellent  
pH .....8.0 - 90  
Recoat .....Very good  
Shelf life .....1 year  
Specific gravity..... 1.04

**Warranty**

This product is not intended for public use and is intended for use by trained, professional contractors and installers. It is warranted to be of uniform quality, within manufacturing tolerances. The manufacturer has no control over the use of this product, therefore, no warranty, expressed or implied, is or can be made either as to the affects or as results of such use. In any case, the manufacturer’s obligations shall be limited to refunding the purchase price or replacing material proven to be defective. The end user shall be responsible for determining product’s suitability and assumes all risks and liability.

**Manufacturer**

Legacy<sup>™</sup> Decorative Concrete Systems  
A Division of Solomon Colors, Inc.

4050 Color Plant Rd.  
Springfield, IL 62702

Tel. 217-522-3112  
Toll Free 800-624-0261  
Fax. 800-624-3147

**Legacy<sup>™</sup> Distribution Centers**

4050 Color Plant Rd.  
Springfield, IL 62702

1251 West Durst Rd.  
Rialto, CA 92376

670 Allen Rd.  
Carlisle, PA 17013